

DINO GRIP FLAT SHEET

Data Sheet

DESCRIPTION

Dino Grip Flat Sheet is a high-performance safety Flat Sheet made from high quality GRP (glass reinforced plastic) / FRP (fibre reinforced plastic). They are designed to be installed on any flat surface to provide an instant non-slip surface.

CHARACTERISTICS

- Slip Resistant Surface
- Class 1 Flame Spread Non-Sparking
- Corrosion Resistant
- Lightweight
- Non-Metallic
- Tough & Durable
- Can be Cut to Size
- Quick Installation

APPLICATIONS

Ideal for the installation on any surface to provide an instant non-slip surface.

TECHNICAL DATA

Description	Slip Resistant Decking Profiles	
Top Finish	Carbon and Silicon Grip Top Surface	
Stock Colors	Black, Yellow and Grey	
Thickness	Nominally 0.16" Thick	
Chemical Resistance	Different Chemical Resistance Available, Please Call our Technical Department for Advice	
Panel Size	8ft x 4ft	
Flat Sheet Weight	41 Lbs	
Service Temperatures	-4°F to + 176°F	
Load capabilities	Credited with no load bearing strength	
Design Life	10+ Years (subject to traffic analysis)	
General Use	Standard Pedestrian Traffic	

SLIP RESISTANT LEVELS

Measured using the Pendulum test method (Four S rubber slider / 96 Slider) - standard simulated shoe sole.

Top Surface	Dry Reading	Wet Reading
Standard Grit Surface	80	75

The Slip Resistance Group guide to slip resistance of a floor for able bodied pedestrians.

Four S Pendulum Value	Potential For Slip	
Above 65	Extremely Low	
35 to 65	Low	
25 to 65	Moderate	
25 and Below	High	

To ensure that the above slip resistant levels are maintained the Flat Sheet should be kept clean in accordance with our cleaning guide and tips.

Richco International | Tele: 1-888-848-4157 | Email: info@dinogrip.com